

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CM 1139 PART A (colors)
PRODUCT CODES: 1139 A (colors)

MANUFACTURER: QuestMark Flooring, Div. Of Centimark Corporation
STREET ADDRESS: 12 Grandview Circle
CITY, STATE, ZIP: Canonsburg, PA 15317

INFORMATION PHONE: 724-743-7777
EMERGENCY PHONE: Chemtrec 800-424-9300

PREPARED BY: Thomas McElwaine

DATE REVISED: 7/20/2014

Chemical Name or Class: Epoxy mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 4, Acute dermal toxicity category 4, Skin corrosion category 2, skin sensitizer category 1B, Serious eye irritation category 2B, Acute toxicity inhalation category 4, Carcinogenicity category 1, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Health hazard, Exclamation Mark, Aquatic Toxicity

Warning: Harmful if swallowed

Warning: Harmful in contact with skin

Warning: Harmful if inhaled

Warning: Causes skin irritation

Warning: Causes eye irritation

Warning: May cause allergic skin reaction:

Danger: May cause cancer

Toxic to aquatic life with long lasting effects

Risk Phrases:

R20 Harmful by inhalation

R21/22 Harmful in contact with skin and if swallowed

R22 Harmful if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin

R42/43 May cause sensitization by inhalation and skin contact

R45 May cause cancer

R52 Harmful to aquatic organisms

R66 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P234 Keep only in original container.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

HMIS HAZARD CLASSIFICATION

HEALTH: 2 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **PERSONAL PROTECTIVE EQUIPMENT:** B

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES.

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: yes

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B.

Some Colors may Contain Titanium Dioxide. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A	25068-38-6	NONE	NONE	NONE	
ALKYL GLYCIDYL ETHER	68609-97-2	NONE	NONE	NONE	
additive NJTSRN 800963-5023)	NONE	NONE	NONE		<1.0
Siloxanes and silicones, di-me reactions products with silica (non-hazardous)	67762-90-7	none	none	none	
siloxanes and silicones, di-methyl (non-hazardous)	63148-62-9	none	none	none	
Carbon black (in colors)	1333-86-4	3.5 ppm	3.5 ppm	none	<1.0
Titanium Dioxide (in colors)	13463-67-7	10mg/m3	10mg/m3	5mg/m3	<3.0

SECTION 3 NOTES:

No toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present.

Note: Ingredients listed without percentages, the percentages are considered a trade secret

SECTION 4: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE IMMEDIATELY CONSULT A PHYSICIAN.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR,
(% by volume)

UPPER: not available
LOWER: not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NO UNUSUAL FIRE HAZARDS KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING, SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID – AMBER CLEAR or COLORS

BOILING POINT OR RANGE: 200+ F

VAPOR DENSITY (AIR = 1): Not available

SPECIFIC GRAVITY (H₂O = 1): 1.1

EVAPORATION RATE: not available

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A

Decomposition Temperature: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO₂, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component additive NJTSRN 800963-5023: Acute oral toxicity: LD50 rat>8,000,000 mg/kg; skin irritation rabbit – no skin irritation

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B.

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

SECTION 12: ECOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component Carbon LD50 – Intravenous, mouse = 440 mg/kg

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, MARINE POLLUTANT

SECTION 15: REGULATORY INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;

Component additive NJTSRN 800963-5023: on TSCA List. Not a California Prop 65 chemical

Component Siloxanes and silicones, di-me reactions products with silica: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component siloxanes and silicones, di-methyl: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List. Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS

Component Carbon: Contains Proposition 65 Chemicals. Carbon: is listed on TSCA and DSL Canada

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

EPA SARA Title III Section 313 components above the de minimus level: none

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CM 1139 PART B (colors)
PRODUCT CODES: 1139 B (colors)

MANUFACTURER: QuestMark Flooring, Div. Of Centimark Corporation
STREET ADDRESS: 12 Grandview Circle
CITY, STATE, ZIP: Canonsburg, PA 15317

INFORMATION PHONE: 724-743-7777
EMERGENCY PHONE: Chemtrec 800-424-9300

PREPARED BY: Thomas McElwaine

DATE REVISED: 7/20/2014

Chemical Name or Class: Polyamine mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 5, Acute dermal toxicity category 4, Skin corrosion category 2, skin sensitizer category 1B, Serious eye damage category 1, Acute toxicity inhalation category 4, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Aquatic Toxicity

Hazard Statements:

Warning: Harmful if swallowed
Warning: Harmful in contact with skin
Warning: Causes skin irritation
Warning: May cause an allergic skin reaction
Danger: Causes serious eye damage
Warning: Harmful if inhaled
Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Risk Phrases:

R20 Harmful by inhalation
R21/22 Harmful in contact with skin and if swallowed
R22 Harmful if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin
R42/43 May cause sensitization by inhalation and skin contact
R52 Harmful to aquatic organisms
R53 May cause long-term adverse effects in the aquatic environment
R66 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P234 Keep only in original container.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 Wear respiratory protection.

HMIS HAZARD CLASSIFICATION

HEALTH: 2 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **PERSONAL PROTECTIVE EQUIPMENT:** G

POTENTIAL HEALTH EFFECTS

EYES:

WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN:

NONE KNOWN

INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
METHYLENEDI(CYCLOHEXYLAMINE)	1761-71-3	NONE	NONE	NONE	
NONYL PHENOL	25154-52-3	NONE	NONE	NONE	
ALIPHATIC POLYAMINE NJTSRN 05995500-	H2390U	NONE	NONE	NONE	

SECTION 3 NOTES: (*) *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR,
(% by volume)

UPPER: not available
LOWER: not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

PRODUCT CODE: 1139 (colors)

RESPIRATORY PROTECTION: NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: AMBER CLEAR LIQUID WITH AMINE ODOR

BOILING POINT OR RANGE: 560+F

VAPOR DENSITY (AIR = 1):N/A

SPECIFIC GRAVITY (H₂O = 1): 1.0

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A

Decomposition Temperature: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO₂, NOX

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute health hazard

Ingestion: LD50: > 1,620 mg/kg, species – rat (estimated)

Inhalation: LC50 (1 hr): > 20 mg/l, species – rat (estimated)

Skin: LD50: . 1000 mg/kg, species rabbit (estimated)

Eye irritation Severe eye irritant

Acute dermal irritation: Severe skin irritant, corrosive to the skin of a rabbit.

Sensitization: May cause sensitization by skin contact

CHRONIC HEALTH HAZARD

The product or a component may be mutagenic, the data is inconclusive.

SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: no data available

Toxicity to fish (component nonyl phenol LD50 (96h): 0.128 mg/l – species fathead minnow.

Toxicity to fish: (component (METHYLENEDI(CYCLOHEXYLAMINE) LC50 (96h) 46-100 mg/l – species Golden Orfe

Toxicity to daphnia – component nonyl phenol – EC50 (48h) 0.19 mg/l

Toxicity to daphnia – component METHYLENEDICYCLOHEXYLAMINE – EC50 (48h) 6.84 mg/l

Toxicity to Algae: Component METHYLENEDICYCLOHEXYLAMINE EC50 (72h) 140-200 mg/l

Bioaccumulation – no data availavable for the product itself; component nonyl phenol is a moderate bioaccumulation potential.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING O FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 10 NOTES:

SECTION 14: Transport Information

DOT: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III

IMO/MDG: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III, MARINE POLLUTANT

SECTION 15: REGULATORY INFORMATION

EPA SARA Title III components above de minimus level: None

Does not contain California Proposition 65 chemicals.

All components on the DSL list, EINECS, DSL, AICS, ENCS, ECL, SEPA and PICCS list or inventory.

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

SAFETY DATA SHEET

PRODUCT CODE: 1139

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CM 1139 PART A
PRODUCT CODES: 1139 A

MANUFACTURER: QuestMark Flooring, Div. Of Centimark Corporation
STREET ADDRESS: 12 Grandview Circle
CITY, STATE, ZIP: Canonsburg, PA 15317

INFORMATION PHONE: 724-743-7777
EMERGENCY PHONE: Chemtrec 800-424-9300

PREPARED BY: Thomas McElwaine

DATE REVISED: 7/20/2014

Chemical Name or Class: Epoxy mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 4, Acute dermal toxicity category 4, Skin corrosion category 2, skin sensitizer category 1B, Serious eye irritation category 2B, Acute toxicity inhalation category 4, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity

Warning: Harmful if swallowed
Warning: Harmful in contact with skin
Warning: Harmful if inhaled
Warning: Causes skin irritation
Warning: Causes eye irritation
Warning: May cause allergic skin reaction:
Toxic to aquatic life with long lasting effects

Risk Phrases:

R20 Harmful by inhalation
R21/22 Harmful in contact with skin and if swallowed
R22 Harmful if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin
R42/43 May cause sensitization by inhalation and skin contact
R52 Harmful to aquatic organisms
R66 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P234 Keep only in original container.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P285 In case of inadequate ventilation wear respiratory protection.

HMIS HAZARD CLASSIFICATION

HEALTH: 2 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **PERSONAL PROTECTIVE EQUIPMENT:** B

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES.

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

SAFETY DATA SHEET

PRODUCT CODE: 1139

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
RESPIRATORY INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A	25068-38-6	NONE	NONE	NONE	
ALKYL GLYCIDYL ETHER additive NJTSRN 800963-5023)	68609-97-2 NONE	NONE NONE	NONE NONE	NONE	
Siloxanes and silicones, di-me reactions products with silica (non-hazardous)	67762-90-7		none	none	<1.0
siloxanes and silicones, di-methyl (non-hazardous)	63148-62-9	none	none	none	

SECTION 3 NOTES:

No toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present.

Note: Ingredients listed without percentages, the percentages are considered a trade secret

SECTION 4: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE IMMEDIATELY CONSULT A PHYSICIAN.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, **UPPER:** not available
(% by volume) **LOWER:** not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NO UNUSUAL FIRE HAZARDS KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING, SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID – AMBER CLEAR

BOILING POINT OR RANGE: 200+ F

VAPOR DENSITY (AIR = 1): Not available

SPECIFIC GRAVITY (H₂O = 1): 1.1

EVAPORATION RATE: not available

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A

Decomposition Temperature: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO₂, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component additive NJTSRN 800963-5023: Acute oral toxicity: LD50 rat>8,000,000 mg/kg; skin irritation rabbit – no skin irritation

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

SECTION 12: ECOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

SECTION 13: WASTE DISPOSAL

SAFETY DATA SHEET

PRODUCT CODE: 1139

WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/MDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, MARINE POLLUTANT

SECTION 15: REGULATORY INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;

Component additive NJTSRN 800963-5023: on TSCA List. Not a California Prop 65 chemical

Component Siloxanes and silicones, di-me reactions products with silica: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component siloxanes and silicones, di-methyl: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

EPA SARA Title III Section 313 components above the de minimus level: none

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

SAFETY DATA SHEET

PRODUCT CODE: 1139

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CM 1139 PART B
PRODUCT CODES: 1139 B

MANUFACTURER: QuestMark Flooring, Div. Of Centimark Corporation
STREET ADDRESS: 12 Grandview Circle
CITY, STATE, ZIP: Canonsburg, PA 15317

INFORMATION PHONE: 724-743-7777
EMERGENCY PHONE: Chemtrec 800-424-9300

PREPARED BY: Thomas McElwaine

DATE REVISED: 7/20/2014

Chemical Name or Class: Polyamine mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 5, Acute dermal toxicity category 4, Skin corrosion category 2, skin sensitizer category 1B, Serious eye damage category 1, Acute toxicity inhalation category 4, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Aquatic Toxicity

Hazard Statements:

Warning: Harmful if swallowed
Warning: Harmful in contact with skin
Warning: Causes skin irritation
Warning: May cause an allergic skin reaction
Danger: Causes serious eye damage
Warning: Harmful if inhaled
Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Risk Phrases:

R20 Harmful by inhalation
R21/22 Harmful in contact with skin and if swallowed
R22 Harmful if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin
R42/43 May cause sensitization by inhalation and skin contact
R52 Harmful to aquatic organisms
R53 May cause long-term adverse effects in the aquatic environment
R66 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P234 Keep only in original container.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 Wear respiratory protection.

HMIS HAZARD CLASSIFICATION

HEALTH: 2 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **PERSONAL PROTECTIVE EQUIPMENT:** G

POTENTIAL HEALTH EFFECTS

EYES:

WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN:

NONE KNOWN

INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

SAFETY DATA SHEET

PRODUCT CODE: 1139

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
METHYLENEDI(CYCLOHEXYLAMINE)	1761-71-3	NONE	NONE	NONE	
NONYL PHENOL	25154-52-3	NONE	NONE	NONE	
ALIPHATIC POLYAMINE NJTSRN 05995500-	H2390U	NONE	NONE	NONE	

SECTION 3 NOTES: (*) *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR,
(% by volume)

UPPER: not available
LOWER: not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

PRODUCT CODE: 1139

RESPIRATORY PROTECTION: NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: AMBER CLEAR LIQUID WITH AMINE ODOR

BOILING POINT OR RANGE: 560+F

VAPOR DENSITY (AIR = 1):N/A

SPECIFIC GRAVITY (H₂O = 1): 1.0

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A

Decomposition Temperature: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO₂, NOX

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute health hazard

Ingestion: LD50: > 1,620 mg/kg, species – rat (estimated)

Inhalation: LC50 (1 hr): > 20 mg/l, species – rat (estimated)

Skin: LD50: . 1000 mg/kg, species rabbit (estimated)

Eye irritation Severe eye irritant

Acute dermal irritation: Severe skin irritant, corrosive to the skin of a rabbit.

Sensitization: May cause sensitization by skin contact

CHRONIC HEALTH HAZARD

The product or a component may be mutagenic, the data is inconclusive.

SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: no data available

Toxicity to fish (component nonyl phenol LD50 (96h): 0.128 mg/l – species fathead minnow.

Toxicity to fish: (component (METHYLENEDI(CYCLOHEXYLAMINE) LC50 (96h) 46-100 mg/l – species Golden Orfe

Toxicity to daphnia – component nonyl phenol – EC50 (48h) 0.19 mg/l

Toxicity to daphnia – component METHYLENEDICYCLOHEXYLAMINE – EC50 (48h) 6.84 mg/l

Toxicity to Algae: Component METHYLENEDICYCLOHEXYLAMINE EC50 (72h) 140-200 mg/l

Bioaccumulation – no data availavable for the product itself; component nonyl phenol is a moderate bioaccumulation potential.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING O FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 10 NOTES:

SECTION 14: Transport Information

DOT: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III

IMO/MDG: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III, MARINE POLLUTANT

SECTION 15: REGULATORY INFORMATION

EPA SARA Title III components above de minimus level: None

Does not contain California Proposition 65 chemicals.

All components on the DSL list, EINECS, DSL, AICS, ENCS, ECL, SEPA and PICCS list or inventory.

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation